

MUTCD NUMBER R7

CODE R30A



Arrow Direction: Left, right or both; specify when ordering.

\* NOTE: TIMES ARE VARIABLE, SPECIFY WHEN ORDERING.  
FOR ARROWHEAD DIMENSIONS, SEE APPENDIX PAGE 2 OF 11, STANDARD ARROWHEAD.

| SIGN    | DIMENSIONS (INCHES) |    |     |     |     |       |       |       |       |       |     |       |       |     |   |       |     |       |     |       |       |
|---------|---------------------|----|-----|-----|-----|-------|-------|-------|-------|-------|-----|-------|-------|-----|---|-------|-----|-------|-----|-------|-------|
|         | A                   | B  | C   | D   | E   | F     | G     | H     | J     | K     | L   | M     | N     | P   | Q | R     | S   | T     | U   | W     | X     |
| MINIMUM | 12                  | 18 | 1/4 | 1/4 | 7/8 | 3 1/2 | 1 1/8 | 5 1/4 | 1 1/2 | 6 3/8 | 3/8 | 2 1/2 | 1 3/4 | 3/4 | 1 | 1 5/8 | 3/8 | 2 1/8 | 3/4 | 7 3/4 | 9 1/2 |

COLOR  
BORDER & LEGEND - RED (REFL)  
BACKGROUND - WHITE (REFL)

- THE POLICY FOR INTENDED USAGE OF THIS SIGN IS SHOWN ON THE REVERSE SIDE -

*MR. [Signature]*  
Dep CHIEF, DIVISION OF TRAFFIC ENGINEERING

3/22/91  
DATE

7/13/93  
REVISION

REVISION